

# JCB VIBROMAX VALJCI

Ubrzajte gradnju sa  
naprednim tandem i  
tamponskim valjcima



**ODMAH  
DOSTUPNO**



**NAJNOVIJA  
TEHNOLOGIJA ZA  
EFIKASNO I BRZO  
ZBIJANJE TERENA**



**JEDNOSTAVNO  
DNEVNO  
ODRŽAVANJE**



**AUTOMATSKA  
KONTROLA  
VIBRACIJE**

## **116D** **TAMPONSKI VALJAK**

- ✓ Zatvorena ROPS/FOPS kabina sa rasvjetom za rad i vožnju
- ✓ Klima i grijanje u kabini
- ✓ JCB dieselmax motor sa malom potrošnjom
- ✓ Mogućnost montaže "JEŽ" obloge
- ✓ Integrisani uređaj za mjerenje stišljivosti tla

## **CT 260-120** **TANDEMSKI VALJAK**

- Preklopivi ROPS okvir ✓
- Provjereni Kubota motor sa malom potrošnjom ✓
- Dobra preglednost ✓
- Poklopac za zaštitu instrument table ✓
- Rezervoar za vodu i napredni sistem prskalica ✓



# CT260-120 | 116D

## TANDEMSKI VALJAK - JCB CT260-120

Motor	Kubota 4-taktni sa tri cilindra i vodenim hlađenjem Stage V Bez AD Blue i DPF filtera
Operativna težina	2560 kg
Širina valjica	1200 mm
Statično linerano opterećenje (naprijed/nazad)	10.5 kg/cm <sup>2</sup>   10.9 kg/cm <sup>2</sup>
Snaga motora	18 kW
Frekvencija (naprijed/nazad)	50Hz / 66Hz
Centrifugalna sila (naprijed/nazad)	23.6 kN / 41.1kN



**AKCIJSKA CIJENA**



**AKCIJSKA CIJENA**

## TAMPONSKI VALJAK JCB 116D

Motor	JCB DIESEL MAX 4-taktni sa četircilindra i vodenim hlađenjem Tier 3; Bez AD Blue i DPF filtera
Operativna težina	11.920 kg
Širina valjica	2.100 mm
Statično linerano opterećenje (naprijed/nazad)	34.2 kg / cm <sup>2</sup>
Snaga motora	85 kW
Frekvencija (naprijed/nazad)	36Hz
Centrifugalna sila (naprijed/nazad)	256 kN / 147 kN
Radna brzina kretanja	0 - 5 km/h
Vozna brzina kretanja	0 - 10.5 km/h
Dimenzija guma	23.1 - R26

\*Ponuda je ograničena i vrijedi do isteka zaliha.



**KONTAKTIRAJTE NAS**

**Enir Trgo**

+387 61 148 987

e.trgo@terra-world.ba

**Tarik Kamenjašević**

+387 61 487 261

t.kamenjasevic@terra-world.ba

